


# APZ13-750 Modular

## Shower drain



### Application

For wheelchair access  
 For drainage of floor-level showers  
 For installation into open spaces or near the wall of the shower area  
 For the perforated stainless steel grids, grid INSERT for embedding tiles, full grid

SPACE and prismatic grid STREAM

For indoor use

For traps APZ-S6, APZ-S9 and APZ-S12

### Features

- Shower drain material: stainless steel 1.5 mm, AISI 304, DIN 1.4301
- Shower drain made from one piece of stainless steel sheet
- Linear drain from stainless steel (hardened by pickling, passivation and electrochemical polishing)
- Self-adhesive tape for quality waterproofing
- Gradient of inner part of the shower drain body
- Installation height from 54 mm
- The shower drain body is protected by the polystyrene insert
- Adjustable height
- 25 years guarantee

### Scope of supply

- Installation channel cover
- Protective foil covering for the drain edges and odour trap
- Self-adhesive waterproofing tape
- Linear shower drain

### Order number, Logistic information

Code	EAN		Weight (kus   packing   palett)	Dimensions (piece   packing)	Quantity (packing   palett)
APZ13-750	8595580551513	750 mm	1,8538   35,2760   125,8280 kg	840×156×84   mm	20   60 pcs

### Guarantee

2/25 years

### Customs code

73249000

### Technical specifications

- Load class K3 300 kg